

New Tyre 340-457 (13.00-18) For APC BTR-80 (KI-80)

Technical Specifications	
BTR 80 Tyre Applications	Ural-4320 / GAZ -66 / Trucks / BTR-80
Tyre Model:	New Tyres (KI-80)
Tyre Size:	13.00-18 (340-457)
Execution:	TL
Disc Diameter:	18.0 Inches
Scuffing of Tyre:	97 m3 / TDj, 350cm3/kw.hr
Thickness of Distance Ring:	150 - 460 mm
Tread Type:	Extreme
Season:	All Season
Tread:	Cross Country
Pattern Type	Directional
Design:	Tubeless
Layering:	8 Layers
Max Load Index:	18.2 KN (1820 kgf)
Max Speed Index:	Max Speed 80 km/h or 50 mp/h
Pressure at Max Load kPa:	350-370 Load
Recommended Rim	254-463
Outer Diameter:	1120 +/- 1%
Profile Width:	400 +/- 10%
Weight:	112 -118 kg
Complete Tyre Set Items	
Tyre Bel-80N:	13.00-18 (340-457)
Spacer Ring:	260-460
Runflat:	Bullet Proof Insert
Samples Required	
Vehicle Test:	Model of Vehicle Required (Full Set Tyres)
Laboratory Test:	Official Laboratory Required (3 rd Party)
Minimum Bulk Order Quantities Tyres	
1. 20 Foot Shipping Container. Each 20ft container loads about 50 tyres pieces.	
2. 40 Foot Shipping Container. Each 40 ft container loads about 120 tyre pieces.	
Delivery Timescales	
Each 40 ft container will take about 30 days of production after payment, or 50% deposit. BCS only sell genuine BTR-80 Tyres and Accessories.	
Samples Available	
All samples are payable upfront	
BTR-80 Tyre Warranty	
1. Guarantee for tyres is 12 months or 5000 km of use.	
2. All tyres are a return to manufacturer, unless previously agreed other term.	
3. Export Documents includes full documentation, customs clearance for export.	
4. Tyres have passed a set of verification tests, including laboratory and field conditions.	