

New Tyre 1150x400-457 For APC BTR-80 (KI-126)

Technical Specifications	
BTR 80 Tyre Applications	Ural-4320 / GAZ -66 / Other Trucks / APC BTR-80
Tyre Model:	New Tyres (KI-126)
Tyre Size:	15.5-18 (1150x400-457)
Execution:	TL
Disc Diameter:	18.0 Inches
Scuffing of Tyre:	97 m3 / TDj, 350cm3/kw.hr
Thickness of Distance Ring:	Not Known
Tread Type:	Extreme
Season:	All Season
Tread:	Cross Country Ability
Pattern Type	Directional
Design:	Tubeless
Layering:	8 Layers
Max Load Index:	2180 Kg
Max Speed Index:	135/136 G/F Max Speed 80 -90 km/h or 56 mp/h
Pressure at Max Load kPa:	350-370
Recommended Rim	302-457
Outer Diameter:	+ 1% - 1 150 +/-10
Profile Width:	400 mm +/- 10%
Weight:	134 kgs
Complete Tyre Set Items	
Tyre:	15.5-18 (1150x400-457)
Spacer Ring:	260-460
Runflat:	Bullet Proof Insert
Samples Tyres	
Vehicle Test:	Model of Vehicle Required (Full Set Tyres)
Laboratory Test:	Official Laboratory Required (3 rd Party)
Minimum Bulk Order Quantities Tyres	
1. 20 Foot Shipping Container. Each 20ft container loads about 50 tyres pieces.	
2. 40 Foot Shipping Container. Each 40 ft container loads about 120 tyre pieces,	
Delivery Timescales	
Each 40 ft container will take about 30 days of production after payment, or 50% deposit. BCS only sell genuine BTR-80 Tyres and Accessories.	
Samples Available	
All samples are payable upfront	
BTR-80 Tyre Warranty	
1. Guarantee for tyres is 12 months or 5000 km of use.	
2. All tyres are a return to manufacturer, unless previously agreed other term.	
3. Export Documents includes full documentation, customs clearance for export.	
4. Tyres have passed a set of verification tests, including laboratory and field conditions.	